



Phone (201) 507-9100 - Fax (201) 507-0447

January 2019

### **UVI Statement**

Ultraviolet light, oxygen, and heat all will degrade polyolefins and cause brittleness, color change, and product failure. However, there are additives called UVI (ultraviolet inhibitors) that trap the free radicals which form during the photo-oxidation process thus retarding the breakdown of the polyolefin. Sigma Stretch Film does use UVI in certain films to extend the outdoor life of the product. The product codes on these special items are MUV, MUB, and MBI.

The number of wraps, film thickness, humidity, sun intensity, prestretch level, chemical exposure, pollution, and storage conditions are just a few of the many variables that will affect the life of UV inhibited plastic wrap. Sigma Stretch Film cannot control these variables and therefore cannot guarantee the useful life of this film. However, the UV products have been engineered using an instrument that attempts to duplicate nature and accelerate the weathering process. By doing this, a correlation is drawn between film life and exposure to UV light. The industry standard is presently a retained elongation of 50% after 1600 hours in the accelerated weathering tester. UV inhibited films from Sigma Stretch Film contain appropriate types and levels of UVI concentrate to conform to this standard. As a reference, 2000 hours is generally accepted as one year in the Southern Florida sun. It should also be noted that the test is performed with unstretched 80 gauge film under laboratory conditions and will vary depending on the variables mentioned earlier. Sigma Stretch Film recommends and requires a minimum thickness of 80 gauge and a maximum stretch level of 150% for optimum protection.

Please contact your Sigma Stretch Film Representative for further information.

A handwritten signature in black ink, appearing to read "Jeff Garcia", is positioned above the printed name.

Jeff Garcia  
Technical Manager  
Sigma Stretch Film