



PRESTRETCH HAND FILM

- Strength and cling of blown film in an easy-to-use ergonomic light weight roll.
- Prestretch promotes more consistent, optimized film usage and reduces user fatigue.
- High containment at thin gauges results in less plastic in the environment.
- Reduced worker fatigue ensures pallets are wrapped the same throughout shift. Walk forward application is safer than conventional film application.
- Damage proof rolls.
- Extended core for easy application, no applicator necessary!
- Applications include: cold environments, distribution and grocery warehouse, internal wrapping, boxed products, food processors, hand wrap applications, all load profiles, and bagged products.
- 100% Recyclable.

PO Box 808, Lyndhurst, NJ 07071

☎ 201-507-9100 | 📠 201-507-0447

stretch.info@sigmaplastics.com | www.sigmastretchfilm.com

Sigma Stretch Film is a division of the Sigma Plastics Group of Companies and is a Certified Minority Owned Company.

39 GAUGE					
Product	Width (mm)	Length (M)	Case Weight (LBS)	PKG	Rolls/Pallet
HPE1615ECO	385	450	14.5	Boxed	48
HPE1615ECOB	385	450	3.63	Bulk	180
HPE1815ECO	445	450	16.1	Boxed	48
33 GAUGE					
Product	Width (mm)	Length (M)	Case Weight (LBS)	PKG	Rolls/Pallet
HPE1415ECO2	347	450	10.9	Boxed	48
HPE1615ECO2	385	450	12.1	Boxed	48
HPE1615ECO2B	385	450	3.02	Bulk	189
HPE1620ECO2B	385	610	4.09	Bulk	180
HPE1815ECO2	445	450	13.6	Boxed	48
HPE1815ECO2B	445	450	3.41	Bulk	126
HPE1820ECO2B	445	610	4.62	Bulk	120
29 GAUGE					
Product	Width (mm)	Length (M)	Case Weight (LBS)	PKG	Rolls/Pallet
HPE1415ECO3	347	450	9.6	Boxed	48
HPE1415ECO3B	347	450	2.4	Bulk	177
HPE1615ECO3	385	450	10.6	Boxed	48
HPE1615ECO3B	385	450	2.65	Bulk	118
HPE1620ECO3B	385	610	3.6	Bulk	112
HPE1815ECO3	445	450	12	Boxed	48
HPE1815ECO3B	445	450	3	Bulk	118
HPE1820ECO3B	445	610	4.06	Bulk	112
24 GAUGE					
Product	Width (mm)	Length (M)	Case Weight (LBS)	PKG	Rolls/Pallet
HPE1615ECO4	385	450	8.8 / Case	Boxed	48
HPE1615ECO4B	385	450	2.2 / Roll	Bulk	126

More sizes and gauges are available. Your Sigma Sales Pro will be pleased to discuss your requirements.

2 WEEK LEAD TIME

