

MSC TWO-SIDED CLING MACHINE FILM .60 mil

Product Description

Sigma Select is a double-sided cling cast machine stretch film ideal for general purpose wrapping. Economically wrap pallets without sacrificing load stability, film clarity, or cling. Available in 20 and 30 inch widths.

Applications

Beverage industry Bagged products Boxed products Paper rolls General purposes A/B-load profiles



Film Properties	Typical Value (English)	Tolerance	Test Method
Tensile Strength at Yield MD	1250 psi	± 15%	ASTM D882
Tensile Strength at Yield TD	1200 psi	± 15%	ASTM D882
Tensile Strength at Break MD	6800 psi	± 15%	ASTM D882
Tensile Strength at Break TD	4100 psi	± 15%	ASTM D882
Elongation at Break MD	390%	± 15%	ASTM D882
Elongation at Break TD	610%	± 15%	ASTM D882
Protrusion Puncture	9.5 lbs.	± 15%	ASTM D5748
Protrusion Puncture Energy	18.0 in-lb	± 15%	ASTM D5748
Elmendorf Tear Strength MD	350 g/mil	± 15%	ASTM 1922
Elmendorf Tear Strength TD	630 g/mil	± 15%	ASTM 1922
Cling - Outside to Inside @ 225%	min 150 g/in	± 15%	ASTM D5458

Dimensions	Value	Tolerance	
Core ID	3.05 inches	± 0.05%	
Film Thickness	15.2 micron		

Manufactured with pride in the USA and Canada by Sigma Stretch Film

Page & Schuyler Aves. Bldg #8 Phone: 800-672-9727 • 201-507-9100 Email: stretch.info@sigmaplastics.com Visit our website at www.sigmastretchfilm.com ©Copyright 2018 Sigma Stretch Film