





CAST MACHINE FILM

- High prestretch quality. Optimum performance when pre-stretched between 250% 300%.
- Two-sided cling cast machine film.
- Applications include: bagged products, food processors, most A/B-load profiles, light to moderate weight loads, distribution warehouses, automatic equipment, high speed overhead equipment, boxed product, items prone to crush.
- 100% Recyclable.

20 INCH				
Product	Length	Gauge	Roll Weight (LBS)	Rolls/ Pallet
MFC2045100	4,500′	1.00 mil	36.0	40
MFC206080	6,000′	.80 mil	38.4	40
MFC206075	6,000′	.75 mil	36.0	40
MFC206070	6,000'	.70 mil	33.6	40
MFC206065	6,000'	.65 mil	31.2	40
MFC208055	8,000′	.55 mil	35.2	40
30 INCH				
Product	Length	Gauge	Roll Weight (LBS)	Rolls/ Pallet
MFC306075	6,000'	.75 mil	54.0	20
MFC306065	6,000′	.65 mil	46.8	20
MFC308055	8,000′	.55 mil	52.8	20

More sizes and gauges are available. Your Sigma Sales Pro will be pleased to discuss your requirements.

PO Box 808, Lyndhurst, NJ 07071 ☎ 201-507-9100 | 墨 201-507-0447 stretch.info@sigmaplastics.com | www.sigmastretchfilm.com

Sigma Stretch Film is a division of the Sigma Plastics Group of Companies and is a Certified Minority Owned Company.