

## MVA ONE-SIDED CLING BIO-ASSIMILATION CAST MACHINE FILM 1.20 mil

## **Product Description**

Vanish is our revolutionary, high-performance one-sided cling cast film powered by Smart Plastic Technology's Eclipse Bio-assimilation Technology. Designed to completely bio-assimilate back into nature without leaving behind any plastic microparticles. 100% recyclable. Available in 500mm and 750mm widths.

## **Applications**

Light pallet High-speed wrapping One-sided cling required



Film Properties	Typical Value (English)	Tolerance	Test Method
Tensile Strength at Yield MD	1250 psi	± 15%	ASTM D882
Tensile Strength at Yield TD	1150 psi	± 15%	ASTM D882
Tensile Strength at Break MD	6500 psi	± 15%	ASTM D882
Tensile Strength at Break TD	3800 psi	± 15%	ASTM D882
Elongation at Break MD	540%	± 15%	ASTM D882
Elongation at Break TD	640%	± 15%	ASTM D882
Protrusion Puncture	14.5 lbs.	± 15%	ASTM D5748
Protrusion Puncture Energy	37.3 in-lb	± 15%	ASTM D5748
Elmendorf Tear Strength MD	290 g/mil	± 15%	ASTM 1922
Elmendorf Tear Strength TD	590 g/mil	± 15%	ASTM 1922
Cling - Outside to Inside @ 225%	min 150 g/in	± 15%	ASTM D5458

Dimensions	Value	Tolerance	
Core ID	3.05 inches	± 0.05%	
Film Thickness	30.5 micron		

## Manufactured with pride in the USA and Canada by Sigma Stretch Film

Page & Schuyler Aves. Bldg #8 Phone: 800-672-9727 • 201-507-9100 Email: stretch.info@sigmaplastics.com Visit our website at www.sigmastretchfilm.com ©Copyright 2018 Sigma Stretch Film