Sigma Stretch Film®



BLOWN MACHINE FILM

- High durability multi-layer one-sided cling blown machine film designed to handle the most demanding applications.
- Stiff formula combined with strong puncture resistance make it ideal for securing heavy, tough to secure, A, B, and C loads.
- Opportunity to reduce film thickness while increasing containment force.
- One-sided cling makes Vortex ideal for high speed applications.
- 100% Recyclable.



500mm						
Product	Length	Micron	Roll Weight (kgs)	Rolls/Pallet		
MVT5001230	1220	30.5	17.2	40		
MVT5001425	1430	25.6	16.8	40		
MVT5001523	1525	23.1	16.1	40		
MVT5001820	1830	20.5	17.2	40		
MVT5001917	1980	17.9	16.3	40		

750mm						
Product	Length	Micron	Roll Weight (kg)	Rolls/Pallet		
MVT7501230	1220	30.5	25.9	20		
MVT7501425	1430	25.6	25.3	20		
MVT7501523	1525	23.1	24.3	20		
MVT7501820	1830	20.5	25.9	20		
MVT7501917	1980	17.9	24.5	20		

More sizes and gauges are available. Your Sigma Sales Pro will be pleased to discuss your requirements.

PO Box 380, 290 Jamieson Bone Road, Belleville, ON K8N 585 ☎ 613-966-4400 | ♣ 613-966-2058 stretch.info@sigmaplastics.com | www.sigmastretchfilm.com

Sigma Stretch Film is a division of the Sigma Plastics Group of Companies and is a Certified Minority Owned Company.

