



BLOWN MACHINE FILM

- *Maximum load containment and puncture resistance.*
- *Designed for bonding between layers and reduced tailing.*
- *Performs well in extreme environments such as extreme cold, dusty and outdoor. Ideal for heavy C type loads.*
- *Applications include: heavy bagged products, magazines and papers, roofing materials, liquids, high containment applications, unstable B/C load profiles, cold environments, irregular shaped loads, heavy weight loads, brick and block, and large/heavy bagged items.*
- **100% Recyclable.**

20 INCH				
Product	Length	Gauge	Roll Weight (LBS)	Rolls/Pallet
MPB2040120	4,000'	1.20 mil	38.4	40
MPB2044100	4,400'	1.00 mil	35.2	40
MPB205090	5,000'	.90 mil	36.0	40
MPB205080	5,000'	.80 mil	32.0	40
MPB206080	6,000'	.80 mil	38.4	40
MPB206070	6,000'	.70 mil	33.6	40

More sizes and gauges are available. Your Sigma Sales Pro will be pleased to discuss your requirements.

PO Box 808, Lyndhurst, NJ 07071

☎ 201-507-9100 | 📠 201-507-0447

stretch.info@sigmaplastics.com | www.sigmastretchfilm.com

Sigma Stretch Film is a division of the Sigma Plastics Group of Companies and is a Certified Minority Owned Company.

