



Sigma Summit ultra-performance, one-side cling film performs at its peak on high speed equipment.

Sigma Summit is engineered to stretch up to 300% due to an easy unwind which makes it ideal for high speed, high pre-stretch equipment. The uncompromising state-of-the-art cling package promotes the adhesion of all film layers, while the no-cling surface on the outside allows pallets to touch and remain intact when pulled apart. This saves space in trucks and warehouses.

Applications Include:

- Bagged Products
- Boxed Products
- Fully Automatic Equipment
- Bundling Applications
- High Speed Overhead Equipment
- Loads Requiring 1-sided Cling
- Loads Requiring Film Clarity
- A, B, and C-Load Profiles
- Inboard/Outboard Loads
- Distribution Center Mixed Pallets
- Light to Heavy Weight Containers

Film Width(mm)	Roll Length	Film Gauge	Roll Weight	Rolls/Pallet	Product Number
500	5,000'	.90 mil	35.4 lb	40	MIT5005090
750	5,000'	.90 mil	53.1 lb	20	MIT7505090
500	6,000'	.80 mil	37.8 lb	40	MIT5006080
750	6,000'	.80 mil	56.7 lb	20	MIT7506080
500	7,000'	.65 mil	35.8 lb	40	MIT5007065
750	7,000'	.65 mil	53.7 lb	20	MIT7507065
500	8,000'	.55 mil	34.6 lb	40	MIT5008055
750	8,000'	.55 mil	52.0 lb	20	MIT7508055

Your Sigma Sales Pro will be pleased to discuss your requirements.