


SIGMA
SUMMIT

Cast Film

Applications Include:

Bagged Products
 Boxed Products
 Fully Automatic Equipment
 Bundling Applications
 High Speed Overhead Equipment
 Loads Requiring 1-sided Cling
 Loads Requiring Film Clarity
 A, B, and C-Load Profiles
 Inboard/Outboard Loads
 Distribution Center Mixed Pallets
 Light to Heavy Weight Containers

**Sigma Summit ultra-performance, one-side
 cling film performs at its peak on high speed
 equipment.**

Sigma Summit is engineered to stretch up to 300% due to an easy unwind which makes it ideal for high speed, high pre-stretch equipment. The uncompromising state-of-the-art cling package promotes the adhesion of all film layers, while the no-cling surface on the outside allows pallets to touch and remain intact when pulled apart. This saves space in trucks and warehouses.

Film Width	Roll Length	Film Gauge	Roll Weight	Rolls/Pallet	Product Number
20"	4,500'	1.05 mil	37.8 lb	40	MIT2045105
30"	4,500'	1.05 mil	56.7 lb	20	MIT3045105
20"	5,000'	.90 mil	36.0 lb	40	MIT205090
30"	5,000'	.90 mil	54.0 lb	20	MIT305090
20"	6,000'	.80 mil	38.4 lb	40	MIT206080
30"	6,000'	.80 mil	57.6 lb	20	MIT306080
20"	7,000'	.65 mil	36.4 lb	40	MIT207065
30"	7,000'	.65 mil	54.6 lb	20	MIT307065
20"	8,000'	.55 mil	35.2 lb	40	MIT208055
30"	8,000'	.55 mil	52.8 lb	20	MIT308055

Your Sigma Sales Pro will be pleased to discuss your requirements.

Σ Sigma Stretch Film

PO Box 808, Lyndhurst, NJ 07071

T: 201-507-9100 F:201-507-0447

www.sigmastretchfilm.com

Email: stretch.info@sigmaplastics.com

Sigma Stretch Film is a division of the Sigma Plastics Group of Companies and is a Certified Minority Owned Company.